

Prepared (Subject resp) ETHBAAT Jenö Balasko		No. 1/1531-CRL 113 200/5 Uen		
Approved (Document resp) ETHLEL Elemer Lelik	Checked ETHGRY	Date 2016-06-02	Rev PF2	Reference

Installation Guide for the TITAN TTCN-3 Test Executor



Abstract

This document describes the detailed information of installing TITAN TTCN-3 Test Executor and all of its components.

Copyright

Copyright (c) 2000-2016 Ericsson Telecom AB.
All rights reserved. This program and the accompanying materials are made available under the terms of the Eclipse Public License v1.0 which accompanies this distribution, and is available at

<http://www.eclipse.org/legal/epl-v10.html>.

Disclaimer

The contents of this document are subject to revision without notice due to continued progress in methodology, design and manufacturing. Ericsson shall have no liability for any error or damage of any kind resulting from the use of this document.

Prepared (Subject resp) ETHBAAT Jenő Balasko		No. 1/1531-CRL 113 200/5 Uen		
Approved (Document resp) ETHLEL Elemer Lelik	Checked ETHGRY	Date 2016-06-02	Rev PF2	Reference

Contents

1 Introduction.....3

1.1 Overview3

1.2 Target Groups3

1.3 Typographical Conventions3

1.4 Prerequisites3

1.5 Installing Prerequisites on Cygwin (on Windows).....4

2 Installation6

2.1 Downloading the Software6

2.2 Installing the Package7

2.3 Install TITAN with Clang8

3 Setting the User Environment9

3.1 Environmental Variables9

3.2 Modification of the User Login Script.....9

3.3 Modifying Makefile Library.....10

4 Licensing11

4.1 Obtaining License Key (Only for Ericsson users).....11

4.2 Installing the License Key.....12

5 References13

Prepared (Subject resp) ETHBAAT Jenö Balasko		No. 1/1531-CRL 113 200/5 Uen		
Approved (Document resp) ETHLEL Elemer Lelik	Checked ETHGRY	Date 2016-06-02	Rev PF2	Reference

1 Introduction

1.1 Overview

This document describes obtaining the TITAN TTCN-3 Test Executor software, installing the Test Executor and all of its components, setting the user environment, and licensing mechanism.

1.2 Target Groups

This document is for all audience who intend to create and execute simulations.

1.3 Typographical Conventions

This document uses the following typographical conventions:

- **Bold** is used to represent graphical user interface (GUI) components such as buttons, menus, menu items, dialog box options, fields and keywords, as well as menu commands. Bold is also used with '+' to represent key combinations. For example, **Ctrl+Click**
- The '/' character is used to denote a menu and sub-menu sequence. For example, **File / Open**.
- `Monospaced font` is used represent system elements such as command and parameter names, program names, path names, URLs, directory names and code examples.
- **bold monospaced font** is used for commands that must be entered at the Command Line Interface (CLI), For example, `ttcn3_start`

1.4 Prerequisites

The supported platforms are Solaris, Linux and Cygwin (on Windows platforms).

The following are required for proper operation of the TITAN:

- Openssl-0.9.8k
- Libxml-2.7.1
- JDK 1.5.0_10 or later (only required if the JNI-based executor in the Executor plug-in is used. JNI cannot be used on Cygwin.)

Note: if the platform has other, but compatible, version of above tools, TITAN will be built with those.

Prepared (Subject resp) ETHBAAT Jenö Balasko		No. 1/1531-CRL 113 200/5 Uen		
Approved (Document resp) ETHLEL Elemer Lelik	Checked ETHGRY	Date 2016-06-02	Rev PF2	Reference

On Linux, the platform-supplied versions of OpenSSL and libxml2 are used. OpenSSL is usually installed by default. The libxml2 package may need to be installed manually.

To create executable test suites, the development packages of OpenSSL, which contain C language headers and libraries, and libxml2 also need to be installed with the package manager of platform. The development packages should be called openssl-dev (or -devel) or libopenssl-dev (or -devel) and libxml2-dev (or -devel) respectively.

To deploy the prerequisites is special on Cygwin therefore it is discussed below.

1.5 Installing Prerequisites on Cygwin (on Windows)

To deploy the prerequisites is special on Cygwin therefore it is discussed below.

Titan is always built on the newest Cygwin version available.

- If Cygwin has been installed already, refresh your Cygwin installation. Start the Cygwin setup utility (see below). It will refresh your installed Cygwin packages to the newest versions.
- If Cygwin hasn't been installed yet:
 - 1 Download and execute the latest Cygwin installer utility depending on your platform and the Titan package to be downloaded:
32-bit version: <https://cygwin.com/setup-x86.exe>
64-bit version: https://cygwin.com/setup-x86_64.exe
 - 2 Select Install from Internet (recommended to save local disk place)
 - 3 Choose Cygwin installation root directory (C:\cygwin is recommended).
 - 4 Select All users or Just Me.
 - 5 Select "Local Package Directory" (typically the same directory, where the setup...exe Cygwin installer utility is stored).
 - 6 Use Internet Explorer Proxy Settings (recommended).
 - 7 Select a download mirror site.
 - 8 In the package selection dialog you can select different views to find the required packages easier and you can search the packages via the search field. The Cygwin installer will automatically select the packages which the manually selected ones are depending on. Do not deselect any automatically selected package!
There are three hierarchical levels of minimally required packages, depending on Your task:
 - 8.1 test execution only(from command line or from Eclipse Titan Executor):

Prepared (Subject resp) ETHBAAT Jenö Balasko		No. 1/1531-CRL 113 200/5 Uen		
Approved (Document resp) ETHLEL Elemer Lelik	Checked ETHGRY	Date 2016-06-02	Rev PF2	Reference

Base: <All packages> (Default setting of the installer)
Net: openssl
Tcl: expect

- 8.2 Test case development: in addition to the above select the following packages:
Devel: binutils
Devel: gcc-g++
Devel: make
Libs: libxml2-devel
Net: openssl-devel (automatically installs Net:openssl as well, if selected)
- 8.3 To compile your own Titan Cygwin binary: in addition to the above, select the following packages:
Devel: bison
Devel: ctags (optional)
Devel: cygwin32-expat
Devel: diffstat
Devel: flex
Devel: gcc-core
Editors: <any editor of your preference> e.g vi, nedit, xemacs, gedit, nano and so on
Libs: libncurses-devel
Libs: libreadline-devel

If, after selecting the required packages and clicking on the "Next" button, a "Resolving Dependencies" window lists further required packages, ensure that the "Select required packages (RECOMMENDED)" checkbox is checked and click on the "Next" button.

9 Select the "Create" icon on the Desktop checkbox

10 (Optional)

Your "unix" home directory, by default is: <your cygwin installation directory>/home/<yourUserId>. If you are (also) working in command line mode, it is a good practice to change this to the folder where your TTCN-3 projects are located. Edit the file <your cygwin installation directory>/etc/passw: In the line: ourUserId:unused:<xxxxxx>:<yyyyy>:U-<yourDomain>\<yourUserId>, S-1-5-21-nnnnnn...nnnnn:/home/<yourUserId>:/bin/bash replace "/home/<yourUserId>" with the folder of your preference.

Note: you can access all Windows drives from Cygwin as /cygdrive/<windowsDriveLetter>".

Example: to set your "unix" home directory to the "My_Home" folder within your Windows Documents folder, you should replace "/home/<yourUserId>" by

"/cygdrive/c/Users/<yourUserId>/Documents/My_Home"

WARNING: The path of your "unix" home directory shall not contain any

Prepared (Subject resp) ETHBAAT Jenö Balasko		No. 1/1531-CRL 113 200/5 Uen		
Approved (Document resp) ETHLEL Elemer Lelik	Checked ETHGRY	Date 2016-06-02	Rev PF2	Reference

space!

Note: It is not a requirement, but is a kind of best practice to place Titan into a subfolder within your "unix" home directory.

- 11 When installation is finished, add the `$CYGWIN_INSTALL_DIRECTORY\bin` directory to the PATH environment variable of Windows, so Eclipse will access the shell commands.
For example if the cygwin root is "C:\cygwin64" then "Path" should contain "C:\cygwin64\bin".
- 12 To check if your installation is correct, open either a Cygwin shell (use the desktop icon created during Cygwin installation or start `bash.exe` from the Windows Start menu) or start `cmd.exe` from the Windows Start menu and type:
`bash.exe`

2 Installation

This chapter describes obtaining the software and installing it.

2.1 Downloading the Software

Download the Titan package for your platform, OS and GCC version from <https://projects.eclipse.org/projects/tools.titan/downloads>

A binary distribution, suitable for the used operating system (Solaris, Linux, FreeBSD or Windows NT/9x¹) and for a C++ compiler, in a tar-gzip archive will be received.

Warning: the version of C++ compiler used is important. If the version difference between the system's compiler and the compiler that the basic TTCN-3 library was built with is large enough, the linking of executable test suites will fail with strange error messages. The reason is the different mapping of C++ class and (polymorphic) member function names into linker symbols.

For example, this problem persists between versions 2.8.x and 2.95.x of GCC. Different C++ compilers (e.g. Sun Workshop and GCC) are, of course, totally incompatible. The solution for this problem is to use nearly the same version of the C++ compiler as the binary package was built with.

Binaries for other operating systems or C++ compilers are available only on request.

¹ For using TITAN on Windows platforms, installing the Cygwin programming environment is required see chapter 1.4.1 Installing Prerequisites on Cygwin (on Windows)

Prepared (Subject resp) ETHBAAT Jenö Balasko		No. 1/1531-CRL 113 200/5 Uen		
Approved (Document resp) ETHLEL Elemer Lelik	Checked ETHGRY	Date 2016-06-02	Rev PF2	Reference

2.2 Installing the Package

No administrator (root) privileges are required for installation, but the install directory must be readable for all users of the test executor. Perform the following steps to install TITAN:

- 1 Create an empty directory, for example, `/usr/local/TTCN3` or `/home/<UserId>/TTCN3`. This directory will be referred as `$TTCN3_DIR` in the further sections of this document.
- 2 Copy the `.tgz` file into this directory.
- 3 Unpack all files from the archive using any of the following commands (assuming GNU tar):

```
tar xvzf ttcn3-<version>-<platform>-<compiler>.tgz  
or  
gzip -dc ttcn3-<version>-<platform>-<compiler>.tgz |  
tar -xvf -
```

The following sub-directories are created:

- `bin` contains the executable programs: the Compiler, the Makefile Generator, the Main Controller for parallel test execution and two log formatter utilities.
- `etc` contains a demo license key, which enables to use the parser parts of the Compiler by any user on any host, that is, without C++ code generation. The installation can be tested with this demo key until the personalized license key is received.
- `include` contains the C++ header files needed to compile the generated C++ code.
- `lib` contains the pre-compiled Base Library for use with the generated C++ code both for single and parallel mode in static and dynamic linking² formats.
- `man` contains UNIX manual pages (for the Compiler and the Makefile Generator).
- `demo` contains a simple TTCN-3 test suite ("Hello, world!") together with a sample test port and a compiled executable.
- `doc` contains this documentation in PostScript and PDF formats.

To complete the TITAN TTCN-3 Test Executor installation, some environmental variables should be set and the login script should be modified.

² Note that not all platforms support dynamic linking.

Prepared (Subject resp) ETHBAAT Jenö Balasko		No. 1/1531-CRL 113 200/5 Uen		
Approved (Document resp) ETHLEL Elemer Lelik	Checked ETHGRY	Date 2016-06-02	Rev PF2	Reference

Note: the C++ source code generated by this version (patch level) of Compiler is not compatible with older versions of TTCN-3 Base Library and vice versa.³

If upgrading TITAN from an older version, all modules of existing test suites must be re-translated with the new compiler in order to make them running with the new libraries.

It is recommended to make a backup copy of the older version of the distribution. There are some minor incompatibilities in the compiler's grammar that may cause many syntax errors in TTCN-3 modules that were translated correctly with earlier versions.

2.3 Install TITAN with Clang

Currently it is experimental to use TITAN with clang on Ubuntu operating system. It was tested only on Ubuntu. In order to use TITAN with clang on Ubuntu some steps must be done:

1. Install **clang-3.8** (3.8 is the required version).
2. Go into your TITAN installation directory and open (or create) the Makefile.personal file and add the following lines:
CXX := clang++-3.8
CC := clang-3.8
3. If TITAN is already compiled run **make distclean** command
4. To compile TITAN with clang run **make** and **make install** commands.

There are some important notes about using clang with TITAN:

- The C++ source code generated and TITAN must be compiled with the same version of clang. See section 2.2 note.
- Makefiles of TTCN-3 projects must be modified by hand (replace **CXX = g++** with **CXX = clang++3.8**). Or regenerated using **makefilegen**, to use clang compiler. TITAN's **makefilegen** can detect if it was compiled with clang and will generate makefiles with clang as default C++ compiler.
- Required clang version is **3.8**.

³ Sometimes even the linking fails; but a successful linking does not mean that everything is correct at all.

Prepared (Subject resp) ETHBAAT Jenö Balasko		No. 1/1531-CRL 113 200/5 Uen		
Approved (Document resp) ETHLEL Elemer Lelik	Checked ETHGRY	Date 2016-06-02	Rev PF2	Reference

3 Setting the User Environment

This chapter describes the environment variables that must be set, and the modification of the user login scripts.

3.1 Environmental Variables

The following environmental variables should be set:

- With system administrator privileges, set the `$TTCN3_DIR` environment variable in the common `/etc/profile` and add the `$TTCN3_DIR/bin` directory to the system paths.
- All tools of TITAN, including the Executable Test Suites, require a shared library of OpenSSL (`libcrypto.so`) for execution. To avoid incompatibilities, the suitable shared object file is provided in `$TTCN3_DIR/lib`, so add `$TTCN3_DIR/lib` to the `LD_LIBRARY_PATH` environment variable.
Warning: If this step is not performed, the compiler will not start!
- Add `$TTCN3_DIR/man` to the `$MANPATH` environment variable to reach the manual pages directly.
- If there is no valid license key, refer to [Licensing](#). If upgrading from an older version with a license key valid for this version, skip this step.
- To run TITAN, ensure that the `$TTCN3_DIR` environmental variable has been set, for example, assuming a `tcsh` as login shell:

```
setenv TTCN3_DIR /usr/local/TTCNv3
```
- To use the TTCN-3 keyword help feature in the GUI with a web browser other than the default Netscape, it is necessary to set the `$TTCN3_BROWSER` environmental variable, for example, to specify Opera, type the following at the C-shell:

```
setenv $TTCN3_BROWSER opera
```

After setting the environmental variables, the TITAN TTCN-3 Test Executor installation is complete.

3.2 Modification of the User Login Script

The following examples provide some help in modifying the login scripts.

Example modifications of login script assuming bash as login shell:

```
TTCN3_DIR=/usr/local/TTCNv3
PATH=$PATH:$TTCN3_DIR/bin
LD_LIBRARY_PATH=$LD_LIBRARY_PATH:$TTCN3_DIR/lib
MANPATH=$MANPATH:$TTCN3_DIR/man
TTCN3_LICENSE_FILE=/home/tmpusr/license.dat
export TTCN3_DIR PATH LD_LIBRARY_PATH MANPATH TTCN3_LICENSE_FILE
```

Example modifications of login script assuming tcsh as login shell:

Prepared (Subject resp)		No.		
ETHBAAT Jen0 Balasko		1/1531-CRL 113 200/5 Uen		
Approved (Document resp)	Checked	Date	Rev	Reference
ETHLEL Elemer Lelik	ETHGRY	2016-06-02	PF2	

```
setenv TTCN3_DIR /usr/local/TTCNv3
setenv PATH ${PATH}:${TTCN3_DIR}/bin
setenv LD_LIBRARY_PATH ${LD_LIBRARY_PATH}:${TTCN3_DIR}/lib
setenv MANPATH ${MANPATH}:${TTCN3_DIR}/man
setenv TTCN3_LICENSE_FILE /home/tmpusr/license.dat
```

3.3 Modifying Makefile Library

Make sure that the Makefile contains the following highlighted part:

```
SOLARIS8_LIBS = -lxnet -lxml2 -lresolv -lnsl -lsocket
LINUX_LIBS = -lxml2 -lpthread -lrt
```

Prepared (Subject resp) ETHBAAT Jenö Balasko		No. 1/1531-CRL 113 200/5 Uen		
Approved (Document resp) ETHLEL Elemer Lelik	Checked ETHGRY	Date 2016-06-02	Rev PF2	Reference

4 Licensing

This chapter describes how to obtain and install a TITAN license key.

From version 1.1.pl8, TITAN can be used only with a valid license key.

4.1 Obtaining License Key (Only for Ericsson users)

The license keys are **free of charge** and can be ordered via an HTML form on the following URL:

Request a Titan licence at:

<https://ericoll.internal.ericsson.com/sites/Titan/Pages/TitanLicenses.aspx>

The personalized license key is a simple ASCII text file, which is sent as an e-mail attachment.

Example of license file:

```
-----BEGIN TTCN-3 LICENSE FILE-----
AAAAAUrhbm9zIFpvbHThbiBTemFi8wAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA
AAAAAFN6YWJvLkphbm9zQGV0aC5lcmljc3Nvbi5zZQAAAAAAAAAAAAAAAAAAAA
AAAAENvbmZvcmlhbmNlIExhYiwgrRXJpY3Nzb24gSHVuZ2FyeSBMdGQuAAAAAAAA
AAAAAEVUSC9STC9TAAAAAAAAAAAAA7ygrgPayP34CzP9B0bXBgc3oAAAAAAAAEAAAB
AAAAAAAAAAEAAABjAAAAYwAAATEAAAAAAAAAADAsAhRmeNSqfy5/3iEHFsBilmiR
+imw2AIUdRN/V3m6gDQzVeMS+wFU13UEeKgAAA==
-----END TTCN-3 LICENSE FILE-----
```

The license key contains the following information encoded in PEM format of OpenSSL library:

A unique identifier (integer number).

If the license needs to be renewed or there are problems with licensing, refer to this `Unique ID`.

- Personal data: user's name, e-mail address, company's name and department.
- The time interval of the license key validity.
- The host ID of the computer where the license is valid on (optional).
- The login name that is allowed to use the tool with this key (optional).
- The type of limitation, that is, host ID, login name or both.
- The version interval of the Test Executor that the license key is valid for.
- The list of features that are enabled by this key (in a bitmask).
- DSA digital signature⁴, which is calculated on all information fields to protect data integrity and make it impossible to modify license information by the user.

⁴ The public key required to check the DSA signature is compiled into all tools and libraries.

Prepared (Subject resp) ETHBAAT Jenó Balasko		No. 1/1531-CRL 113 200/5 Uen		
Approved (Document resp) ETHLEL Elemer Lelik	Checked ETHGRY	Date 2016-06-02	Rev PF2	Reference

4.2 Installing the License Key

Perform the following steps to install the license key:

- Save the license key somewhere in the user home directory. The recommended name for it is `license.dat`, but it can be named alternatively
- It is advised to change its permissions to read-only in order to avoid accidental modification or erasing.
- Set the `TTCN3_LICENSE_FILE` environment variable to point to the license file with full path name. Add this command to the login script to do this step automatically for each login.
- Check the validity of the license by issuing `$TTCN3_DIR/bin/compiler -v`. The compiler will print its version and the information contained in the license file. Also it checks the validity of the license key. Example printout:

```
TTCN-3 and ASN.1 Compiler for the TTCN-3 Test Executor
Product number: CRL 113 200/4 R2A
Build date: Sep 19 2014 10:17:18
Compiled with: GCC 4.8.2
```

```
Copyright Ericsson Telecom AB 2000-2014
```

```
License information:
```

```
-----
License file : /home/ethbaat/license_98.dat
Unique ID    : 98
Licensee     : Attila Balasko
E-mail       : jeno.balasko@ericsson.com
Company      : Ericsson Hungary
Department   : ETH/XZR
Valid from   : Fri Sep 20 00:00:00 2002
Valid until  : Tue Aug 25 23:59:59 2015
Limitation   : USER
Host ID      : 00000000
Login name   : ethbaat
Versions     : from 1.1.pl0 until 1.99.pl99
Languages    : TTCN3 ASN1
Encoders     : RAW TEXT BER PER XER
Applications : CODEGEN TPGEN SINGLE MCTR HC LOGFORMAT
Max PTCs     : 10000
-----
```

```
The license key is valid.
```

```
Using OpenSSL 1.0.1e 11 Feb 2013
```

The last line of the printout indicates the success or the problems with the license key.

If a host-limited key is needed, perform it in the same way but do it as system administrator. Copy it into a common directory, for example `$TTCN3_DIR/etc`, and set `TTCN3_LICENSE_FILE` in the common login script of all users, for example, in `/etc/profile`.

Prepared (Subject resp)		No.		
ETHBAAT Jen0 Balasko		1/1531-CRL 113 200/5 Uen		
Approved (Document resp)	Checked	Date	Rev	Reference
ETHLEL Elemer Lelik	ETHGRY	2016-06-02	PF2	

5 References

- [1] TITAN User Guide
1/198 17-CRL 113 200/5 Uen
- [2] TITAN Programmer's Technical Reference
2/198 17-CRL 113 200/5 Uen